

















Networked Fingerprint Door Controller / Reader

-  World's Best Fingerprint Recognition Technology - Cutting-edge algorithm ranked top in Fingerprint field
-  Live Biometric Sensor - Live Tech Detector
-  Ultra Performance - 1:5000 matches in 1.5 seconds
-  Triple Recognition - Recognition in Terminal only, Server first Recognition
-  Unlimited Template Capacity - 5,000 fingerprints in terminal memory
-  Unlimited using WatchNET Access Software Online
-  Power over Ethernet - Power supply through a single CAT5/6 wiring
-  Multi-Proximity Cards - HID Prox, AWID Prox, EM Prox, WatchNET Prox
-  Exit Reader - Proximity Reader as Out Reader, Connected to Wiegand_In
-  On-Line and Off-Line seamless operation On-Line: Connected to the server
Off-Line: Stand-Alone, not connected to the server

ADVANCED SECURE MODE OF OPERATION

-  No fingerprint picture stored. Proprietary template algorithm.
-  Reader Mode: Door operated by door controller in a secured area.
-  Reader On-Line Mode: No data stored on device.
-  Simple Mode: Doors controlled by WAB-MP-FCS will operate uninterrupted, with or without a network.

| SPECIFICATIONS | |
|-----------------------|---|
| CPU | CPU 32bits ARM®Cortex - M4 Processor |
| Fingerprint Sensor | Semiconductor |
| RF Card Option | P: Proximity, HID, AWID, EM, WatchNET. U: Mifare/DesFire, Mifare Secror, CPU |
| Multi-Proximity Cards | HID, AWID, EM, WatchNET HS |
| Template Capacity | 5000 fingerprints with on device memory. Unlimited using WatchNET Access On-Line |
| Log Capacity | 200,000 |
| User Fingerprint | Up to 3 fingerprints per person |
| Communication | TCP/IP 100MBPS Auto Sensing |
| PoE | 802.3af |
| Authorization Mode | Card / Fingerprint, Fingerprint, Card + Fingerprint |
| Wiegand | Wiegand In & Out |
| Tamper | Switch |
| Operating Temp | -20 C ~ 50 C |
| Operating Voltage | 12vDC, 300mA |
| Dimensions (mm) | W45 x H135 x D58 |
| Certificates | CE, FCC, RoHS |

CANADA:
351 Ferrier Street, Unit 5
Markham, Ontario L3R 5Z2
Canada
Tel: 416-410-6865
Toll Free: 1-866-843-6865

USA:
171 Cooper Ave.
Suite 110, Tonawanda
New York 14150, USA
Tel: 1-716-877-7277
Toll Free: 1-866-843-6865

MIDDLE EAST:
PO Box No 126312
Office Suite 703, Oxford Tower
Business Bay, Dubai, UAE
Tel: + 971 4 2767117

www.watchnetinc.com
info@watchnetinc.com