




4MP WDR IR Dome Network Camera

MPIX-40VDV-IRVR2



Features:

- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- 2.7 mm–13.5 mm Motorized vari-focal lens
- Output 4MP (2560 × 1440)@25/30 fps, max. supports 4MP (2688 x 1520) @ 20 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max IR distance: 40m/131ft
- H.264/H.265
- Rotation mode, WDR(120dB), 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, Line Crossing
- Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
- Supports max. 256 GB Micro SD card
- 12V DC/POE power support
- IP67, IK10 protection grade
- Multiple network monitoring: Built-in web server
- Smart phone compatible



FREE Multisite VMS Software
Download from www.watchnetinc.com


Optional Brackets:



BRACK-WM-48

BRACK-BB-48

BRACK-PM-06



Model	MPIX-40VDV-IRVR2
Camera	
Image Sensor	1/3" 4Megapixel progressive CMOS
Effective Pixels	2688(H) x 1520(V)
Min. Illumination	0.01 Lux @ F1.6
RAM / ROM	128MB / 128MB
Electronic Shutter Speed	Auto/Manual 1/3 s - 1/100000 s
Scanning System	Progressive
IR On / Off Control	Auto / Manual
IR LEDs	2
Lens	
IR Distance	Up to 40m (131ft)
Focal Length	Motorized vari-focal 2.7mm-13.5mm
Max. Aperture	F1.5
Angle of View	Horizontal: 104°-27° Vertical: 5°-15° Diagonal: 124°-31°
Optical Zoom	5 times
Mount Type	φ14
IR On/Off Control	Auto / Manual
Close Focus Distance	0.8 m-0.8 m (2.62 ft-2.62 ft)
Smart Event	
Standard Analytics	Intrusion; Line Crossing
Video	
Compression	H.265; H.264; H.264B; MJPEG
Smart Codec	Supports H.265/H.264
Bit Rate Control	CBR / VBR
Resolution	2688×1520 (2688×1520); 2560×1440 (2560×1440); 2304×1296 (2304×1296); 1080p (1920×1080); 1.3M (1280×960); 720p (1280×720); D1 (704×576/704×480); VGA (640×480); CIF (352× 288/352×240)
Bit Rate	H.264: 32K~6144K / H.265: 12K~ 6144K
Frame Rate	Main Stream: 2688×1520 (1fps-20fps) 2560×1440 (1fps-25/30fps) Sub Stream: 704×576 (1fps-25fps)704×480 (1fps-30fps)
Day / Night	ICR switch
BLC Mode	Yes WDR(120dB)
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto / Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest (ROI)	Yes (4 areas)
Smart IR	Yes
Image Rotation	0°/90°/180°/270° (Supports 90°/270° with 2688 ×1520 resolution)
Mirror	Yes
Privacy Masking	4 areas

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP
Interoperability	ONVIF(Profile S/Profile G/Profile T); P2P
User/Host	20
Edge Storage	WatchNET Cloud; FTP; Micro SD Card (support max. 256 GB); NFS
Browser	IE, Chrome, Firefox
Electrical	
Power Supply	12V DC/POE
Power Consumption	< 6.5W
Environmental	
Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) Less than ≤ 95 %
Storage Conditions	-40° C ~ +60° C (-40° F ~ +140° F)
Ingress Protection	IP67
Vandal Resistance	IK10
Construction	
Casing	Metal
Dimensions	Φ122 mm × 88.9 mm (Φ4.80" × 3.50")
Net Weight	0.45Kg (0.99lb)
Gross Weight	0.58Kg (1.28lb)

*All logos & trade marks represent the registered users only. All rights reserved.
All product specifications on this brochure are subject to change without notice.*

CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-866-843-6865
Local: 1-716-877-7277

Sept 12, 2019
info@watchnetinc.com
www.watchnetinc.com

INDIA:
RZ- 2, Ground Floor
Kapashera
Opp Kapashera Police Station
New Delhi-110037
Tel/Fax: + 91 11 26816005

UAE:
P O Box 126312
No 703, Oxford Towers
Business Bay
Dubai, UAE
Tel: +971 4 2767117