

XVI ENHANCED CVI

MegaPixel over UTP/Coax




XVI-50VDV-IRVDL



5MP CVI IR Dome Camera

Features:


- 1/2.7" 5 Megapixel progressive scan CMOS
- Dual Voltage AC 24V $\pm 25\%$ /DC 12V $\pm 10\%$
- Max. 25 fps@5MP (16:9 video output)
- BLC/HLC/DWDR, 2DNR
- CVI/CVBS/AHD/TVI switchable
- 2.7 mm–12 motorized lens
- Max. IR LEDs length 30m/98.4ft
- IP67, IK10, Smart IR
- Multiple network monitoring:
Built-in web server & Multifunction VMS
- Smart phones compatible, when using compatible DVR



FREE Multisite VMS software
Download from www.watchnetinc.com



Ceiling Mount BRACK-PM-06	Junction Back Box BRACK-BB-48	Wall Mount BRACK-WM-48



Optional Brackets		
BRACK-PM-06 Ceiling Mount	BRACK-BB-48 Junction Back Box	BRACK-WM-48 Wall Mount

Model	XVI-50VDV-IRVDL
Camera	
Image Sensor	1/2.7 5 Megapixel progressive scan CMOS
Effective Pixels	2880 (H) × 1620 (V)
Min. Illumination	0.005 Lux/F1.6, 30IRE, 0 Lux IR on
S/N Ratio	More than 65dB
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s
Illuminator On/Off Control	Auto; manual
IR Distance	30 m (98.4 ft)
IR LEDs	2
Lens	
Lens Type	Motorized vari-focal
Focal Length	2.7 mm–12 mm
Max. Aperture	F1.6
Mount Type	φ14
Angle of View	Horizontal: 34°–107°/ Vertical: 19°–55° / Diagonal: 39°–130°
Iris Type	Fixed iris
Close Focus Distance	0.5 m (1.64 ft)
Auto Focus	N/A
Video	
Resolution	5M (2880 × 1620); 4M (2560 × 1440); 1080p (1920 × 1080); 960H (960 × 576/960 × 480)
Frame Rate	CVI: PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H
Day/Night	Auto switch by ICR
Smart Illumination	Yes
BLC Mode	BLC/HLC/DWDR
WDR	DWDR
Gain Control	Auto / Manual
Noise Reduction	2D NR
White Balance	Auto / Manual
Mirror	Off/On
Privacy Masking	Off/On (8 areas, rectangle)

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.7mm	69m (226.37ft)	27.6m (90.55ft)	13.8m (45.27ft)	6.9m (22.63ft)
	12mm	191.6m (628.6ft)	76.64m (251.44ft)	38.32m (125.72ft)	19.16m (62.86ft)
Port					
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port				
Electrical					
Power Supply	AC 24V ±25%/DC 12V ±10%				
Power Consumption	Max 6.9W (12V DC, IR on)				
Environmental					
Operating Conditions	-30°C ~ +60°C (-22°F ~ +140°F) < 95% (non-condensation)				
Storage Conditions	-30°C ~ +60°C (-22°F ~ +140°F) < 95% (non-condensation)				
Protection Grade	IP67, IK10				
Construction					
Casing	Metal throughout the whole casing				
Dimensions	φ122 mm × 88.9 mm (φ4.8" × 3.5")				
Net Weight	0.47 kg (1.04 lb)				
Gross Weight	0.62 kg (1.34 lb)				

All logos & trade marks represent the registered users only. All rights reserved. All product specifications on this brochure are subject to change without notice.

CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-866-843-6865
Local: 1-716-877-7277

UAE:
PO Box 126312
No 703, Oxford Towers
Business Bay, Dubai, UAE
Tel: +971 4 2767117

Rev. May 04, 2021

info@watchnetinc.com
www.watchnetinc.com