




4MP 40x SENSEFIER IR PTZ AI Network Camera

MPIX-40IRPTZAI



### PRODUCT FEATURES




- 1/1.8" CMOS 4.0MP Full HD Network PTZ Camera
- Powerful 40x optical zoom
- AI Auto Tracking of person and/or Vehicle
- 5.6mm ~ 223mm Focal Length
- SENSEFIER technology
- IR distance up to 500m/1640ft
- Support face recognition
- Deep-learning-based auto tracking and fenced area protection
- Support metadata
- WDR(120dB), Supports Hi-PoE
- Smart wiper
- IP67, Micro SD card 256GB
- iPhone, iPad, Android support

#### Pro AI Functions:

- Face Capture (Detect & Recognition with attributes)
- Fenced Area protection
- People Counting Functions
- Line Crossing (Person & Vehicle Classification)

\* Wallmount Bracket and Power supply included



Wallmount Bracket Included



Optional:  
Water-proof Power Box  
BRACK-PTZ-BOX



Model Number	MPIX-40IRPTZAI
<b>Camera</b>	
Image Sensor	1/1.8" CMOS
Effective Pixels	2560(H) x 1440(V), 4 Megapixels
Scanning System	Progressive
Electronic Shutter Speed	1/1s~1/30,000s
Minimum Illumination	Color: 0.001Lux@F1.4; B/W: 0.0001Lux@F1.4; 0Lux@F1.4 (IR on)
Smart Wiper	Support
IR Distance	Up to 500m (1640ft)
IR On/Off Control	Auto/Manual
IR LEDs	10
<b>LENS</b>	
Focal Length	5.6mm ~ 223mm
Max. Aperture	F1.4 ~ F4.8
Angle of View	H: 63.9° ~ 2.0°; V: 36° ~ 1.3°; D: 68.18° ~ 2.62°
Optical Zoom	40x
Focus Control	Auto/Manual
Iris Control	Auto/Manual
Close Focus Distance	100mm ~ 1000mm
<b>PTZ</b>	
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: -30° ~ 90°, auto flip 180°
Manual Control Speed	Pan: 0.1° ~ 200° /s; Tilt: 0.1° ~ 100° /s
Preset Speed	Pan: 200° /s; Tilt: 120° /s
Presets	300
PTZ Mode	5 Pattern, 8 Tour (up to 32 preset per tour), Auto Pan, 5 Auto Scan
Speed Setup	Human-oriented focal Length/ speed adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
<b>Artificial Intelligence</b>	
Auto Tracking	Support
Face Recognition	Support
Fenced Area Protection	Line Crossing, Intrusion. Support alarm triggering by target types(human and vehicle). Filtering out false alarms caused by animals, rustling leaves, bright lights, etc
Metadata	Support human body, human face, motor vehicle and non-motor vehicle image capture and attributes extraction
<b>General Intelligence</b>	
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
General Intelligence	Object Abandoned / Missing
<b>Audio</b>	
Compression	G.711a/G.711mu/PCM/G.726/AAC/G722.1/G.729/MPEG2-Layer2

<b>Video</b>	
Compression	H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream)
Streaming Capability	3 Streams
Resolution	4M(2592×1520)/3M(2048×1536)/1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/ D1(704×576/704×480)/CIF(352×288/352×240)
Frame Rate	<b>Main stream:</b> 4M/3M/1080P/1.3M/720P(1~25/30fps) <b>Sub stream1:</b> D1/CIF(1 ~ 25/30fps) <b>Sub stream2:</b> 1080P/1.3M/720P(1 ~ 25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.265/H.264: 512K ~ 8192Kbps
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR (120dB)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Motion Detection	Support
Region of Interest	Support
EIS	Support
Optical Defog	Support
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
<b>Network</b>	
Ethernet	RJ-45 (10Base-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, RTCP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1
Interoperability	ONVIF(Profile S/Profile G/Profile T); P2P
Streaming Method	Unicast / Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 256GB
Web Viewer	IE, Chrome, Firefox, Safari
Smart Phone	IOS, Android
<b>Interface</b>	
Video Interface	1 port(BNC, 1.0V[p-p], 75Ω)
RS485	1
Audio I/O	1/1
Alarm I/O	7/2
<b>Electrical</b>	
Power Supply	DC36V/2.23, Hi-PoE
Power Consumption	26W, 42W (Heater on, IR on)
<b>Environmental</b>	
Operating Conditions	-40°C ~ 70°C (-40°F ~ +158°F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A
<b>Construction</b>	
Casing	Metal
Dimensions	Φ262(mm) x 415.6 (mm)
Net/Gross Weight	8.5kg(18.74lb) / 13.5kg(29.76lb)

\* All product names, logos and brands are property of their respective owners. All company products and service names used on this box/website/brochure are for identification purposes only. Use of these names, logos and brands does not imply endorsement. 2022 WatchNET Inc.  
© All Rights Reserved. All product specifications are subject to change without notice.

**CANADA:**  
351 Ferrier Street, Unit 5  
Markham, ON L3R 5Z2  
Toll Free: 1-866-843-6865  
Tel: 416-410-6865

**USA:**  
171 Cooper Ave. Suite 110  
Tonawanda, NY 14150 USA  
Toll Free: 1-866-843-6865  
Local: 1-716-877-7277

**UAE:**  
P O Box 126312  
No 703, Oxford Towers  
Business Bay, Dubai, UAE  
Tel: +971 4 2767117

Rev. Jan. 06, 2022

info@watchnetinc.com  
www.watchnetinc.com