



Resilient  
Reliable  
Robust

## Professional PoE Switch Designed for the Surveillance & Security Industry



PoE/PoE+

30W

Surge



6KV

Total Power  
Budget

≤350W

L3 Managed



### KEY FEATURES

- No noise switch, no heat dissipation fan;
- 350W high-power PoE output;
- Abundant ports: 24 GE PoE+4\*10G(SFP+);
- Support L2/L3 Web management and PoE management;
- Support PoE indicator LED;
- Support high-speed data forwarding, very suitable for large flow of video data forwarding in security surveillance;
- Support fast ring , Self-healing in 20ms Min,
- Quick Installation, convenient for wall/desk/rack installation.

### 24 Ports gigabit 4\*10G uplink L3-managed

The High-power fanless PoE switch(24 ports gigabit 4\*10G uplink L3-managed), which provide 24\*10/100/1000 RJ45 ports, 4\* 1000/10G SFP+ slots.

It supports fanless high-power PoE output (350W). It supports layer-2/3 network management and PoE management.

The products is widely used in security surveillance, network engineering projects, especially in low noise surround such as hotel, office, hospital.

Item	POESW24F
Copper Ports	24* 10/100/1000Base-T PoE RJ45 (Auto-MDI/MDI-X)
SFP Ports	4*1000/10G Base-X SFP (Mini-GBIC)
Console Port	1*RJ45-R232 serial port (115200,8,N,1)
OOB Port	1*10/100Base-TX RJ45 (only used to Web management) default IP:192.168.2.200 name:admin password:admin)
Unit Button	Short press:on/off PoE indicator; >5s restore factory settings
PoE Indicator	Green: PoE output power 0%~70%; Yellow: PoE output power70%~80%; Red: PoE output power 80%~100%
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3Z, IEEE802.3X, IEEE 802.1Q IEEE 802.1p IEEE 802.3ad, IEEE 802.1D, IEEE 802.1X
Switch Fabric	128Gbps / non-blocking
Switch Throughput	95.2Mpps
Switch Architecture	Store and Forward
Shared Data Buffer	1.5Mbit
Address Table	16K MAC address table with auto learning function
Jumbo Frame	10K bytes
PoE Standard	802.3af/at(PSE)
PSE Type	End-span
Power Pin Assignment	1/2(+), 3/6(-)
PoE Power Output	54V DC, 30 watts max
PoE Budget	350 watts max
ESD	6KV Contact discharge 8KV Air discharge Execute: IEC61000-4-2
Power Supply	100~240VAC 50/60Hz, Auto-sensing
Power Dissipation	380W (Including PoE)
Working Temperature	-10°C ~ 50°C / 14°F ~ 122°F
Storage Temperature	-40°C ~ 85°C / -40°F ~ 185°F
Humidity	5% ~ 95% (Non-condensation)
Dimension (LxWxH)	442mm x 320mm x 44.5mm / 17.4" x 12.6" x 1.75"
Weight	6.5kg / 14.33lb
Certificates	CE, FCC, ROHS

Item	POESW24F
<b>Quality of Service</b>	Support COS classification base on 802.1p
	Support QoS base on DSCP
	Support 8 priority queues
	Queue scheduling: SP, WRR, SP+WRR
	Support 802.1p CoS/DSCP priority
<b>Multicast Management</b>	Support SNMPV1 / V2 / V3 protocols
	Support IGMP Snooping
	Support MLD-snooping
<b>POE Management</b>	Support Total Power Control
	Support PoE On Off
<b>Security Features</b>	Support single-port 30W output, Output port and priority
	Supports IP, MAC, port, VLAN binding combinations
	Support MAC address auto-learning, aging and filtration
	Support port isolation, port speed limit
	Support STP \ RSTP \MSTP, Fast-Ring
	Support 5 groups of link aggregation
	Support LLDP, Smart-Link, DLDP
<b>ACL</b>	Support 802.1X
	Support base on source-MAC, target-MAC, protocol-classify, source-IP, target-IP, L4 ports-number
	Support time-range management
	Web-based GUI and CLI management
	Support FTP / TFTP / HTTP load upgrade
<b>System Management</b>	Support traffic statistics
	Support MAC address table query
	Support IP address, DNS server modifications
	Support user name and password modification
	Support for history, log management
	Support System Configuration Backup
	Support to recover the default factory settings on reboot

Item	POESW24F
<b>L3 Management</b>	Support IPV4 static route setup
	Support RIP V1/2 on IPV4
	Support OSPF V1/V2
	Support ISIS on IPV4
	Support BGP on IPV4
	Support static ARP Add,delete,burn-in time sutup/check
	Support static NDAAdd,delete,burn-in time sutup/check
	Support VRRP V1/2/3 virtual redundant route protocol
	Support group-broadcasting PIM,IGMP V1/V2/V3,MLD(IPV4)
	Support relay repeater, DHCP snooping
	Support duplex transfer check mechanism

All product specifications are subject to change without notice.  
All logos & trade marks represent the registered users only. All rights reserved.

**CANADA:**  
351 Ferrier Street, Unit 5  
Markham, Ontario  
L3R 5Z2, Canada  
Tel: 416-410-6865  
Toll Free: 1-866-843-6865

**USA:**  
171 Cooper Avenue, Site 110  
Tonawanda, NY  
14150 USA  
Toll Free: 1-866-843-6865  
Local: 1-716-877-7277

**UAE:**  
P O Box No 126312  
Office Suite 703  
Oxford Towers, Business Bay  
Dubai, UAE  
Tel: + 971 4 2767117

June 15, 2022

[www.watchnetinc.com](http://www.watchnetinc.com)  
[info@watchnetinc.com](mailto:info@watchnetinc.com)