



2MP SENSEFIER IR AI Network PTZ Camera



MPix-21MP5XIRAI

PRODUCT FEATURES

- 1/2.8" 2Megapixel STARVIS™ CMOS
- Sensefier technology
- 2.7 mm–13.5 mm
- IR distance up to 30m/98.43ft
- Deep-learning-based fenced area protection
- Motion Detection
- PoE
- IP66

AI Functions:

- Fenced Area protection
- Line Crossing (Person & Vehicle Classification)



FREE Multisite VMS software
Download from www.watchnetinc.com




Included Brackets/Power Adapter



Wall Mount



Ceiling Mount



Pole Mount Vertical




DC12V/2A
Power Adapter



BRACK-BB-53

Model Number	MPIX-21MP5XIRAI			
Camera				
Image Sensor	1/2.8" CMOS			
Pixel/Max. Resolution	2MP / 1920 (H) x 1080(V)			
Scanning System	Progressive			
Electronic Shutter Speed	1/3 s~1/100000 s			
Minimum Illumination	Color: 0.002 Lux@F1.8 / B/W: 0.0002 Lux@F1.8 0 Lux (illuminator on)			
ROM / RAM	256MB / 512MB			
IR Distance	30m (98.43ft)			
IR On/Off Control	Manual/Smart IR/Off			
IR LEDs	4 IR lights; 1 white light			
LENS				
Focal Length	2.7 mm – 13.5 mm			
Max. Aperture	F1.8 – F3.3			
Angle of View	H: 101.6°–33.5°; V: 52°–18.7°; D: 124.7°–38.5°			
Optical Zoom	5x			
Focus Control	Auto/Semi-Auto/Manual			
Iris Control	Fixed			
Close Focus Distance	1.2m (3.94ft)			
PTZ				
Pan/Tilt Range	Pan: 0°–355° / Tilt: -15°–+90°			
Manual Control Speed	Pan: 0.1°/s–80°/s / Tilt: 0.1°/s–56°			
Preset Speed	Pan: 81°/s; Tilt: 43°/s			
Presets	300			
Power-off Memory	Support			
Idle Motion	Preset			
Artificial Intelligence				
Fenced Area Protection	Line Crossing, and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights,etc.			
Audio				
Compression	G.711a; G.711Mu; G.726; AAC; MPEG2-Layer2; G722.1; G729; G723			
Dori Distance	Detect	Observe	Recognize	Identify
	131m (429.79ft)	52.3m (171.59ft)	26m (85.30ft)	12.8m (41.99ft)
Video				
Compression	H.265; H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream); H.265+; H.264+			
Streaming Capability	3 Streams			
Resolution	1080P (1920 x 1080); 1.3M (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480); CIF (352 x 288/352 x 240)			
	Main stream: 1080P (1–25/30 fps); 1.3M (1–25/30 fps); 720P (1–25/30 fps)			
Frame Rate	Sub stream1: D1/CIF (1–25/30 fps) Sub stream2: 1080P (1–25/30 fps); 1.3M (1–25/30 fps); 720P (1–25/30 fps)			
Bit Rate Control	Variable/Constant			
Bit Rate	H.264: 3 Kbps–20480 Kbps / H.265: 3 Kbps–20480 Kbps			
Day/Night	Auto (ICR)			
BLC / HLC / WDR	Support / Support / DWDR			
White Balance	Auto/Indoor/Outdoor/Tracking/Manual/Sodium lamp/Natural light/Street lamp			
Gain Control	Auto / Manual			
Noise Reduction	DNR (2D/3D)			
Motion Detection	Support			
Region of Interest	Support			
S/N Ratio	≥ 55 dB			
Defog	Electronic			
Flip	180°			
Network				
Ethernet	RJ-45 (10/100Base-T)			
Protocol	IPv4; IPv6; HTTP; HTTPS; 802.1x; QoS; FTP; SMTP; UPnP; SNMP; DNS; DDNS; NTP; RTSP; RTP; TCP; UDP; IGMP; ICMP; DHCP; PPPoE; ARP; SNMP v1/v2c/v3 (MIB-2); RTCP; RTMP			
Interoperability	ONVIF (Profile S&G&T); CGI			
Streaming Method	Unicast / Multicast			
User/Host	20 (total bandwidth: 64MB)			
Storage	FTP; Micro SD card (max. 256 GB); NAS			
Web Viewer	IE7 and later versions/Chrome 42 and earlier versions/Firefox 52 and earlier versions/Safari			
Smart Phone	IOS, Android			
Port				
Audio I/O	1 (Built-in Mic) / 1 (Built-in Speaker)			
Two-way Audio	Support			
Alarm Linkage	Capture; preset; SD card record; send email			
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; encoder state detection; memory card state detection; memory space detection			
Power				
Power Supply	12V DC/2A ± 10% (supports PoE)			
Power Consumption	Basic: 5W/Max: 12W (illuminator on), Power adapter included			
Environmental				
Operating Conditions/Humidity	-30°C to +60°C (-22°F to 140°F) / ≤ 95%			
Ingress Protection	IP66; TVS 2000V lightning proof; surge protection; voltage transient protection			
Structure				
Dimensions	271.7 mm x 142.5 mm x 124.1 mm (10.70" x 5.61" x 4.89")			
Net/Gross Weight	1.1kg (2.43lb) / 1.51kg (3.33lb)			



CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-866-843-6865
Local: 1-716-877-7277

UAE:
P O Box 126312
No 703, Oxford Towers
Business Bay, Dubai, UAE
Tel: +971 4 2767117

November 18, 2022

info@watchnetinc.com
www.watchnetinc.com