


16-Port FE PoE++ 2-Port Gigabit Ethernet Switch



KEY FEATURES:

- Conforms to IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at
- · Provides 16 10/100Base-TX ports and 2 Gigabit Combo ports
- Provides 16 PoE injector and 250W Built-in power supply
- High back-plane bandwidth 7.2 Gbps
- IEEE802.3x Flow control
- Surge protection for power port and data ports
- The switch supports one-key function conversion, currently supports five modes, normal mode, VLAN mode, Extend mode, WATCHDOG mode, QOS mode.



| POWER SUPPLY | |
|--------------------|-----------------------|
| Power supply | Built-in power supply |
| Voltage Range | AC100~240V |
| Switch Consumption | 250W for 16 PoE |

| HARDWARE SPECIFICATIONS | | |
|-------------------------|---|--|
| Downlink Ports | 1~16 Port: 10 /100Mbps | |
| Uplink Ports | 17~18: Gigabit Combo | |
| Transmission Distance | 100Meter(328ft)for RJ-45 2Km 20Km for SFP Port The optical module is optional | |

| SWITCH PROPERTY | | |
|--------------------|--------------------------------------|--|
| Standards | IEEE 802.3/802.3u/802.3ab/802.3af/at | |
| | 14,880pps f or 10Mbps | |
| Transfer Rate | 148,800pps for 100Mbps | |
| | 1,488,000pps for 1000Mbps | |
| MAC Table | 8k | |
| Switching Capacity | 7.2G | |

| | INDICATORS |
|----------|---|
| LINK/ACT | On-Green - The port is connecting Blinks - The port is receiving or transmitting data Off - The port is not linked successfully with the device |

| POE | |
|--------------------|---|
| Lights | On-Green - PD is connected Off - No PD connected or power forwarding fails |
| PoE pin assignment | V+(RJ45 Pin 1,2), V-(RJ45 Pin 3,6) |

| ENVIRONMENT | |
|-------------------------|----------|
| Working Temperature | 0~40°C |
| Storage Temperature | -40~70°C |
| Humidity Non condensing | 0~90% |

| MECHANICAL | |
|------------|------------------|
| Dimension | 440 x 200 x 44mm |
| Color | Gray |

⊕

Power input port INPUT:100-240VAC

Rear Panel



Front Panel

*All logos & trade marks represent the registered users only. All rights reserved. *All product specifications on this brochure are subject to change without notice.



www.watchnetinc.com info@watchnetinc.com

CANADA

351 Ferrier Street Unit 5 Markham, Ontario L3R 5Z2 Tel. 416-410-6865 Toll Free: 1-866-843-6865 USA 171 Cooper Ave. Suite 110 Tonawanda, New York 14150 Tel. 716-877-7277 Toll Free: 1-866-843-6865 MIDDLE EAST PO Box No 126312 Suite 703 Oxford Tower Business Bay, Dubai, UAE Tel. + 971-4-2767117