

























Features:

- 1/2.8" progressive scan CMOS
- Max.5MP(2592×1944) @25/30fps resolution
- · 2.7to 12mm and 5 to 50mm lens optional
- Max.5MP(2592×1944) @25/30fps resolution
- · Support face, human, vehicle detection and capture
- · Intelligent analysis: intrusion, single line crossing, double line crossing, loitering, wrong-way and people counting
- · WDR, 3D DNR, ROI, Defog, HLC
- 1/1 audio input/output, 1/1 alarm input/output
- · Built-in SD card slot
- · Built-in mic and speaker (optional: can be removed)
- · Smart IR distance up to 100 m
- IP66, IK10

Smart Function


- · Supports face, human, vehicle detection and capture
- · Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, People counting
- Support alarm triggering by specified target types (human and vehicle)


Note:

WatchNET NDAA Cameras work only with Blue Series Network Video Recorders



Dimensions(mm)





Optional Accessories



BLS-BB-BUL2 Junction Box



BLS-POLE-27 Pole Mount

Specifications

Camera						
Image Sensor		1/2.8" Progressi	ve Scan CMOS			
Max. Resolution		5MP (2592×1944)				
Electronic Shutter		Auto/Manual, 1/	Auto/Manual, 1/5 ~ 1/20,000s			
Min. illumination		Color: 0.03 Lux @ (F1.6, AGC ON) ,B/W: 0 Lux @ (IR LED ON)				
Day & Night		Auto (ICR)				
Angle Adjustment		Pan: 0° ~ 355°, Tilt: 0° ~ 75°, Rotation: 0° ~ 355°				
Lens	Lens					
Lens Type Motorized for		cus				
Iris	Auto Iris					
Focal Length	2.7 ~ 12 mm		5 to 50mm			
F Number	F1.6 ~ F2.9		F2.0			
		31.1°, V: 71.6° to	H: 46.2° to 7.7°, V: 34.1° to 5.8°			
Image						
Image Adjustment		Brightness, Sharpness, Contrast, Saturation adjustable				
Aisle Mode		Support				
Mirror		Support				
White Balance		Auto/Manual				
Day/Night Setting		Auto, Day, Night, Time				
Smart IR		Support				
Noise Reduction		2D/3D DNR				
Image Enhancement		HLC, BLC, Defog				
Wide Dynamic Range		True WDR				
S/N Ratio		55dB				
Motion Detection		Support				
Privacy Masking		Support				
Video						
Streaming Capabilit		3 Streams				
Stream/Frame Rate		Stream1: 2592×1944, 2592×1520, 1920×1080, 1280×720 @ 25/30fps Stream2: D1, VGA, CIF @ 25/30fps Stream3: VGA, CIF, QVGA @25/30fps				
Bit Rate Control		CBR/VBR				
Bit Rate		Stream1: 200kbps~12Mbps Stream2: 100kbps~6Mbps Stream3: 100kbps~3Mbps				
Region of Interest		Off/On (8 Zone, Rectangle)				
Smart Encode		Support				

Smart Function					
Power Supply		G.711, RAW_PCM			
Power Consumption		64Kbps, 128Kps			
Audio					
Power Supply		G.711, RAW_PCM			
Power Consumption		64Kbps, 128Kps			
Illuminator					
IR Distance	Up to 60m (196.9ft)		Up to 100m (328.1ft)		
IR On/Off Control	Auto/Manual				
Network					
Network Interface		1 Ethernet (10/100 Base-T) RJ-45 Connector			

Network		
Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector	
Built-in Mic & Speaker	Support - Optional	
Audio Interface	1ch Input, 1ch Output	
Alarm Interface	1ch Input, 1ch Output	
Reset Button	Support	
SD Card Slot	Built-in, up to 256GB	

Interface	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP, TLS/SSL
Interoperability	ONVIF, SDK, CGI
Streaming Method	Multicast
Max. User Access	10 Users
Web Viewer	<ie11, chrome,="" firefox<="" td=""></ie11,>
Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian. Default: English
Electrical	
Power Supply	DC12V (-15%~+25%)/POE (IEEE 802.3af)
Power Consumption	Basic: Max 2.5W (IR OFF), Max 6W (IR ON)Max. (Focus + WDR+ Speaker + IR on): 12 W
Operating Temperature	-40°C ~ 55°C (-40°F ~ 131°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP66, IK10
Certifications	CE/FCC
Casing	Metal
Dimensions	φ110 × 356.3mm (φ4.33" × 14.03")
Net Weight	1.45Kg (3.2lb)

*All product names, logos and brands are property of their respective owners. All company products and service names used on this brochure are for identification

purposes only. Use of these names, logos and brands does not imply endorsement.

2022 WatchNET Inc. © All Rights Reserved

All product specifications are subject to change without notice.

Toll Free: 1-866-843-6865