



CE FC



**BLZ-4D180**

### 4 Megapixel Dual Sensor Panoramic turret camera with Dual Light and Active Deterrence



#### KEY FEATURES:

- Dual **4MP** 1/1.8" CMOS sensors for high-definition imaging
- **H.264+ and H.265+ Compression** for efficient video encoding
- **Infrared Range:** Up to 40 meters for clear night vision
- **Warm Light Range:** Up to 40 meters, ensuring optimal visibility in low light
- **Perimeter Protection:** Advanced motion detection with SMD (Smart Motion Detection) support
- **Face Detection and Smart Object Detection** for enhanced security
- **Built-in Mic & Speaker** with Red and Blue LED indicators for added functionality
- **White Light Alarm and Sound Alarm** support for proactive security measures
- Supports up to **256GB Micro SD Card** for ample storage
- **Lens:** 3.6mm fixed lens
- **Power Supply:** 12 VDC or Power over Ethernet (PoE) support
- **IP67 Rating:** Weatherproof and dustproof for reliable outdoor use

| CAMERA                |   |
|-----------------------|---|
| Image Sensor          | 2 x 4MP 1/1.8" CMOS   |
| Max. Resolution       | 8MP, 5120 (H) × 1520 (V)  |
| Scanning System       | Progressive   |
| Electronic Shutter    | Auto/Manual 1/3 s–1/100,000 s   |
| Min. illumination     | 0.0007 lux@F1.6(Color, 30 IRE),0.0004 lux@F1.6 (B/W, 30 IRE),0 lux (Illuminator on) |
| S/N Ratio             | > 56 dB   |
| Illumination Distance | IR distance 40m, Warm light distance 40m<br>2 IR LED + 2 White LED                  |
| Illuminator Control   | Auto; Manual  |

| LENS          |  |
|---------------|--|
| Lens Type     | Fixed lens   |
| Focal Length  | 3.6mm  |
| Max. Aperture | F1.6   |
| Field of View | Horizontal: 0°-180°, Vertical:0°-90°, Diagonal:0°-180° |

| VIDEO             |  |
|-------------------|--|
| Compression       | H.264H; H.264M; H.264B; H.265 MJPEG (Customization)  |
| Smart Compression | H.264H+; H.264M+; H.264B+; H.265+  |
| Bit Rate Control  | CBR/VBR  |
| Bit Rate          | H.264: up to 16384 kbps;<br>H.265: up to 16384 kbps  |
| Stream Capability | 3 Streams  |
| Video Frame Rate  | Main Stream: 5120 × 1520@(1–25/30 fps)<br>Sub Stream: 2048X576 @(1–25/30 fps)<br>Third Stream: 2048X576 @(1–25/30 fps) |
| Day/Night         | Color/B/W  |
| BLC, HLC          | Yes  |
| White Balance     | Yes  |
| Gain Control      | Auto/Manual  |
| WDR               | 120 dB   |
| Noise Reduction   | 3D NR  |
| Motion Detection  | OFF/ON (4 Areas, rectangular)  |
| Mirror            | Yes  |
| Privacy Masking   | 4 Areas  |

| ALARM            |   |
|------------------|---|
| Arming/Disarming | Yes   |
| Sound Alarm      | Yes   |
| Light Alarm      | Red and Blue LED  |
| Alarm Event      | Disconnection; IP Conflict; No SD Card; Capacity Warning; SD Card Error |

| AUDIO             |                                  |
|-------------------|----------------------------------|
| Built-in Mic      | Yes                              |
| Built-in Speaker  | Yes                              |
| Audio Compression | G.711a; G.711Mu; G.726; G.726ASF |

| SMART FUNCTION       |  |
|----------------------|--|
| Intelligent Analysis | Intrusion, Tripwire, loitering detection; people gathering; Parking detection (Support the classification of Vehicle, Human and Non-Motor) |
| Motion Detection     | Support  |
| AI Search            | Work together with NVR   |
| Face Detection       | Face detection; track; snapshot; snapshot optimization   |
| Object Detection     | Abandoned object; Missing object   |
| Heat Map             | Support  |

| NETWORK             |   |
|---------------------|---|
| Network             | RJ-45 (10/100 Base-T)   |
| SDK and API         | Yes   |
| Network Protocol    | TCP/IP;UDP;HTTP;IGMP;ICMP;DHCP;RTP/RTSP ;DNS;DDNS;FTP;NTP;PPPOE;UPNP;SMTP |
| Interoperability    | ONVIF; CGI; P2P(Optional)   |
| User/Host           | 16 (Total bandwidth: 80 M)  |
| Storage             | FTP; Micro SD card (support max. 256 G/FAT32)                             |
| Browser             | IE: IE8 and later; Chrome; Firefox  |
| Mobile Client       | IOS; Android  |
| Management Software | eVMS-BLZ  |

| PORT         |                      |
|--------------|----------------------|
| Audio Input  | 1 channel (RCA port) |
| Audio Output | 1 channel (RCA port) |
| Alarm Input  | 1 channel            |
| Alarm Output | 1 channel            |
| RS485        | Support              |

| ENVIRONMENT          |   |
|----------------------|---|
| Power Supply         | 12V DC (±30%)/PoE (802.3af)                       |
| Power Consumption    | Basic: 4 W ;Max. 14W                              |
| Operating Conditions | –30°C to +60°C (–22°F to +140°F)/Less than 95% RH |
| Storage Conditions   | –40°C to +60°C (–40°F to +140°F)                  |
| Protection Grade     | IP67  |
| Casing               | Metal   |
| Dimensions           | Φ124 mm × 137 mm                                  |
| Net Weight           | 990g  |

| ACCESSORIES |   |
|-------------|---|
| BLZ-BB-140  |  |
| BLZ-WM-140  |  |



\*All logos & trademarks represent the registered users only. All rights reserved.  
\*All product specifications on this brochure are subject to change without notice.

CANADA  
351 Ferrier St. Unit 5  
Markham, Ontario L3R 5Z2  
Tel. +1-416-410-6865  
Toll Free: 1-866-843-6865

USA  
417 Old Falls Blvd.  
N. Tonawanda, NY 14120  
Tel. +1-716-877-7277  
Toll Free: 1-866-843-6865

MIDDLE EAST  
PO Box No 126312  
Suite 703 Oxford Tower  
Business Bay, Dubai, UAE  
Tel. + 971-4-2767117

www.watchnetinc.com  
info@watchnetinc.com