


4K



4x MPIX-50T3MAI Cameras



Kit Contains:

- 1 – ENI-04POE
- 4 – MPIX-50T3MAI
- 1 – USB Mouse

CE Easy auto enroll / plug & play with built-in POE

- Includes everything you need – Just add Ethernet
- 4 Ch Embedded NVR plus 4x 5.0MP Turret Camera
- Plug and Play Setup with Camera Auto Enroll Feature
- Free DDNS, VMS Software, User-Friendly GUI and Web Server



NVR Features:

4 CH with 4 PoE Ports built-in NVR

- Embedded LINUX OS
- Industrial-grade embedded processor
- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps.
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, fenced area protection, IVS, people counting, heat map, and motion detection
- * (AI Features only supported when using AI Cameras)

4 Port POE Built-In

Camera Features:

- 5 Megapixel 1/2.7" CMOS image sensor, low luminance, and high definition image.
- Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps.
- H.265 codec, high compression rate, ultra-low bit rate.
- Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m.
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human).
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.
- Supports max. 256 G Micro SD card; built in MIC.
- 12 vDC/PoE power supply, easy for installation.
- IP67 protection.
- Smart Motion Detection Plus.

AI Functions:

- Fenced Area protection
- AI Motion Detection
- Line Crossing (Person & Vehicle Classification)



FREE Multisite VMS software
Download from www.watchnetinc.com



Technical Specifications ENI-O4POE	
System	
Main Processor	Industrial-grade processor
Operating System	Embedded Linux
Operation Interface	Web, Local GUI
AI	
AI by Recorder	SMD
AI by Camera	Face detection; face recognition; perimeter protection; SMD; people counting; stereo analysis; heat map
Perimeter Protection	
Perimeter Performance of AI by Camera (Number of Channels)	4 channels
Face Detection	
Face Attributes	Gender; age group; glasses; expressions; face mask; beard
Face Detection Performance of AI by Camera (Number of Channels)	All channels (4 targets/s)
Face Recognition	
Face Recognition Performance of AI by Camera (Number of Channels)	All channels (4 targets/s)
SMD Plus	
SMD Plus by Recorder	4 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change
SMD Plus by Camera	All channels (8 targets/s)
Audio and Video	
Access Channel	4 channels
Video Output	1 HDMI, 1 VGA Simultaneous : HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 Heterogeneous : HDMI: 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Port	
Audio Input	1-channel RCA
Audio Output	1-channel RCA
Alarm Input	NA
Alarm Output	NA

Disk Interface	1 SATA port. Each disk can contain up to 20 TB. This limit varies depending on the environment temperature.
USB	2 (1 front USB 2.0 port, 1 rear USB 2.0 port)
HDMI	1
VGA	1
Network Port	1 (10/100 Mbps Ethernet port, RJ-45)
PoE Port	4 ports, 10/100 Mbps, IEEE 802.3 af/at
General	
Power Supply	53 VDC, 1.22 A
Power Consumption	Total output of NVR is <10 W (without HDD) Total output power of PoE is 36 W, the maximum output power of a single port is 25.5 W
Certifications	CE-EMC: EN 55032:2015+A1:2020; EN IEC 61000-3-2:2019+A1:2021; EN 61000-3-3:2013+A1:2019+A2:2021; EN 55035:2017+A11:2020; EN 50130-4:2011+A1:2014 CELV: EN 62368-1:2014

* All product names, logos and brands are property of their respective owners. All company products and service names used on this box/website/brochure are for identification purposes only. Use of these names, logos and brands does not imply endorsement. 2026 WatchNET Inc. © All Rights Reserved All product specifications are subject to change without notice.

Model	MPIX-50T3MAI
Camera	
Image Sensor	1/2.7" CMOS
Max. Resolution	2960 (H) × 1668 (V)
ROM	128 MB
RAM	256 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. illumination	0.007 lux@F1.5 (Color, 30 IRE) 0.0007 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>56 dB
Illumination Distance	up to 30 m (98.43 ft) (IR); up to 30 m (98.43 ft) (Warm light)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	1 warm light + 1 IR LED
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°
Image Sensor	1/2.7" CMOS
Lens	
Max Aperture	F1.6
Focal Length	Fixed 2.8mm lens
Optical Zoom	N/A
Mount Type	M12
Angle of View	Horizontal: 98°; vertical: 72°; diagonal: 130°
Close Focus Distance	0.9m/3ft
Aperture Type	Fixed
Video	
Compression	H.265; H.264; H.264H; H.264B; MJPEG
Smart Codec	Yes
Resolution	5M (2960 × 1668); 4M (2688 × 1520); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Frame Rate	Main Stream: (2960 × 1668@1–20 fps) (2688 × 1520@1–25/30 fps) Sub Stream: (704 × 576@1–25 fps/ 704 × 480@1–30 fps) Third Stream: 1280 × 720@1–25/30 fps
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 3 Kbps–8192 Kbps H.265: 3 Kbps–8192 Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Digital Zoom	N/A
Flip	(Support 90°/270° with 1920 × 1080 resolution)
Mirror	Yes
Privacy Masking	Off / On (4 Area, Rectangle)

Professional Intelligence	
Fenced Area Protection	Line Crossing, Intrusion (Human & Vehicle classification)
Intelligent Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
Audio	
Audio Compression	G.711a; G.711Mu; G726; AAC
Network	
Ethernet	RJ-45 (10/100 Base-T)
Protocol	IPv4;IPv6;HTTP;HTTPS;TCP;UDP;ARP;RTP;RTSP;R TCP;R TMP;SMTP;FTP;SFTP;DHCP;DNS;DDNS;QoS;UPnP ;NTP; Multicast;ICMP;IGMP;NFS;PPPoE;802.1x;SNMP
Interoperability	ONVIF(Profile S/Profile G/Profile T); P2P
Streaming Method	Unicast / Multicast
Max. User Access	20 (Total bandwidth: 64M)
Scene	Yes
Self-adaptation	
Max. User / Host	20 Users (Total bandwidth: 64 M)
Edge Storage	FTP; SFTP; Micro SD Card (support max. 256GB); WatchNET Cloud; NAS
Electrical	
Power supply	12V DC/PoE (802.3af)
Power Consumption	<8.1W
Environmental	
Operating Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / less than≤95%
Storage Conditions	-40°C ~ +60°C (-40°F ~ +140°F)
Ingress protection	IP67
Construction	
Casing	Metal
Dimensions	99.1 mm × Φ121.9 mm (3.9" × Φ4.8")
Net Weight	480 g (1.05 lb)
Gross Weight	660 g (1.45 lb)

** All product names, logos and brands are property of their respective owners. All company products and service names used on this box/website/brochure are for identification purposes only. Use of these names, logos and brands does not imply endorsement. 2021 WatchNET Inc.
© All Rights Reserved. All product specifications are subject to change without notice*

CANADA:
351 Ferrier St. Unit 5
Markham, ON L3R 5Z2
TollFree:1-866-843-6865
Tel. +1-416-410-6865

USA:
417 Old Falls Blvd. Unit A
North Tonawanda
New York 14120
Toll Free:1-866-843-6865
Tel. +1-716-877-7277

UAE:
PO Box 126312
Office Suite 703
Oxford Towers
Business Bay, Dubai
Tel. +971 4 2767117

www.watchnetinc.com
info@watchnetinc.com

AUG 2026